

MODEL: BSX100 Technical Specifications

Task, Pneumatic, Swivel Tilt, Mesh Back, Fixed Arms, Tilt Tension, Tilt Lock



KEY DIMENSIONS

Max. Width.....	29-1/8"
Max. Depth.....	27-7/8"
Max. Height.....	43-1/2"
Seat Size	
Width.....	20-7/8"
Depth.....	17-2/5"-18-3/4"
Height from Floor.....	20-3/8"-24-1/5"
Back Lumbar	
Height.....	9-1/4"

Back Size

Width.....	18-1/2"
Height from Seat.....	24-1/4"

Arm Size

Distance between arms.....	19-1/4"
Height from floor.....	25-1/2" - 32"
Height from seat.....	8-1/2"
Width.....	3-5/8"
Length.....	10"
Arm Set-Back.....	N.A

CONSTRUCTION

Caster..... Black hooded 1.97" diameter dual wheel.

Base..... Black 5 leg injection molded plastic.

Control..... Black heavy gauge steel, swivel tilt, 17-4 taper.

Seat..... 3.5" thick, 9-ply plywood, 2-3/4" thick urethane foam cushion.

Back..... Plastic injection molded.

Upholstery..... See List Pricer.

Arm..... Plastic injection molded, height adjustable.

Chair Weight..... 30.9 pounds.

Shipping Weight... 35.3 pounds.

Shipped..... Assembly required.

Shipping Size..... 24.8" wide x 12.2" deep x 24.4" high (4.3 cubic feet). Shippable by small package carrier.

Flammability

Rating..... Furnished upon request by The HON Company Customer Service. Model BSX100 meets the State of California Department of Consumer Affairs Technical Bulletin 117 requirements.

Special Features.... A pneumatic gas cylinder is used for seating height adjustment of chair.

Note..... All measurements are per BIFMA/CMD procedures.



HONBASYX.com